



## The Relation Between Structure-Performance of Thin Film Composite Membranes and the Tools Used for Their Fabrication Method

Briceno, Kelly; Javakhishvili, Irakli; Guo, Haofei; Villy Christensen, Knud; Norddahl, Birgir; Hvilsted, Søren; Lipnizki, Frank

*Publication date:*  
2016

*Document Version*  
Peer reviewed version

[Link back to DTU Orbit](#)

*Citation (APA):*  
Briceno, K., Javakhishvili, I., Guo, H., Villy Christensen, K., Norddahl, B., Hvilsted, S., & Lipnizki, F. (2016). *The Relation Between Structure-Performance of Thin Film Composite Membranes and the Tools Used for Their Fabrication Method*. Abstract from 26th Annual Meeting of the North American Membrane Society, Bellevue, WA, United States.

---

### General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

## **The relation between structure-performance of thin film composite membranes and the tools used for their fabrication method**

Kelly Briceño <sup>[1]</sup>, Irakli Javakhishvili <sup>[2]</sup>, Haofei Guo <sup>[3]</sup>, Knud Villy Christensen <sup>[1]</sup>, Birgir Norddahl <sup>[1]</sup>, Søren Hvilsed <sup>[2]</sup>, Frank Lipnizki <sup>[3]</sup>

<sup>[1]</sup> Department of Chemical Engineering, Biotechnology and Environmental Technology, University of Southern Denmark, Campusvej 55, 5230 Odense M, Denmark

<sup>[2]</sup> Danish Polymer Centre, Department of Chemical and Biochemical Engineering, Technical University of Denmark, Building 227, 2800 Kongens Lyngby, Denmark

<sup>[3]</sup> R&D department, Business Center Membrane, Alfa Laval A/S, Stavangervej 10, 4900, Nakskov, Denmark

Keywords: Polyamide, thin film composite membranes, fabrication variables, interfacial polymerization.

For more than 30 years polyimides (PA) have been one of the main polymers for the fabrication of thin film composite membranes. Several researchers have assessed the main fabrication variables that influence the final structure of the polyamide layers including monomer concentration, solvents, additives in aqueous and organic phases and type of support to mention a few <sup>[1,2]</sup>. However, few studies have reported the influence of the fabrication tools used in the preparation of the PA layer. Each research group report their own recipe and fabrication method according to the general criteria of avoiding bubble formation during fabrication as that would later compromise the function of the membrane, but each process step must be well controlled to obtain reliable and consistent membrane performance. In general, the fabrication of the polyamide membrane layer is carried out in two steps. A polymeric support is initially brought in contact with the aqueous phase containing *m*-phenylene diamine (MPD) monomer and then with the organic phase containing the trimesoyl chloride (TMC) monomer in order to promote PA formation through interfacial polymerization. The critical step occurs immediately after the support has been in contact with the aqueous phase, because formation of irregular drops could be initiation points for defects during the second step. Several tools have been used to eliminate the drop formation including air-knives, rubber wipers, rubber rollers, glass rollers, or for that matter the absence of any tool using only water evaporation. In this work different methods of avoiding drop formation during the membrane preparation are tested to evaluate how the preparation methods influence the membrane structure and the final membrane properties. Understanding the membrane formation and consequently the defect formation will help to control and reproduce membrane preparation both in laboratory and industrial scale <sup>[3]</sup>. Specifically this work focuses on the preparation of a polyamide membrane layer supported by a polysulfone support after immersion in MPD/aqueous solution followed by immersion in TMC/heptane solution. The polysulfone support is in contact with the MPD/aqueous phase using immersion or pipetting. Further the use of a rubber wiper or absence of any tool to eliminate the aqueous solution droplets is evaluated. Both NaCl rejection and water and NaCl fluxes are evaluated, in order to relate them with the structural characteristics of the membranes using SEM, contact angle and streaming potential.

- [1] Asim K. Ghosh, Byeong-Heon Jeong, Xiaofei Huang, Eric M.V. Hoek , Impacts of reaction and curing conditions on polyamide composite reverse osmosis membrane properties, *Journal of Membrane Science* 311 (2008) 34–45
- [2] Liwei H, McCutcheon J, Impact of support layer pore size on performance of thin film composite membranes for forward osmosis, *Journal of Membrane Science* 483(2015)25–33
- [3] R. Rangarajan, N.V. Desai, S.L. Daga, S.V. Joshi, A. Prakash Rao, V.J. Shah, J.J. Trivedi, C.V. Devmurari, K. Singh, P.S. Bapat, H.D. Raval, S.K. Jewrajka, N.K. Saha, A. Bhattacharya, P.S. Singh, Paramita Ray, G.S. Trivedi, N. Pathak, A.V.R. Reddy, Thin film composite reverse osmosis membrane development and scale up at CSMCRI, Bhavnagar, *Desalination* 282 (2011) 68–77